

UPS Eaton 5P

550VA - 3kVA

120 V y 208/230 V

Núm. de Catálogo	Cap. Nominal (VA/watts)	Conexión de entrada	Receptáculos de salida	Medidas (A x A x P), cm	Peso neto, lb (Kg)
Modelos en tipo torre 120V, 50/60 Hz					
5P750	750/600	5-15P	(8) 5-15R	23,1 x 15,0 x 34,5	22,7 (10,3)
5P1000	1000/770	5-15P	(8) 5-15R	23,1 x 15,0 x 34,5	24,4 (11,1)
5P1500	1440/1100	5-15P	(8) 5-15R	23,1 x 15,0 x 44,5	35,3 (16)
5P2200	1950/1920	5-20P	(4) 5-20R, (4) 5-15R	8,6 x 44,2 x 52,3	65,0 (29,5)
5P3000	3000/2700	L5-30P	(6) 5-20R, (1) L5-30R	8,6 x 44,2 x 64,5	87,0 (39,5)
Modelos en tipo torre 208V ó 230V, 50/60 Hz					
5P850G	850/600	C14 (6)	C13	23,1 x 15,0 x 34,5	21,9 (9,9)
5P1550G	1550/1100	C14 (8)	C13	23,1 x 15,0 x 44,5	35,2 (15,1)
Modelos en tipo rack 2U 120V, 50/60 Hz					
5P1500RT	1440/1440	5-15P	(8) 5-15R	8,6 (2U) x 44,2 x 52,3	65,0 (29,5)
5P2200RT	1950/1920	5-20P	(4) 5-15R, (4) 5-20R	8,6 (2U) x 44,2 x 52,3	65,0 (29,5)
5P3000RT	3000/2700	L5-30P	(3) 5-15R, (3) 5-20R, (1) L5-30R	8,6 (2U) x 44,2 x 64,5	87,0 (39,5)
Modelos en tipo rack 1U 120V, 50/60 Hz					
5P550R	550/420	5-15P	(5) 5-15R	4,3 (1U) x 43,7 x 36,3	17,8 (8,0)
5P750R	750/600	5-15P	(5) 5-15R	4,3 (1U) x 43,7 x 50,8	30,6 (13,9)
5P1000R	1000/770	5-15P	(5) 5-15R	4,3 (1U) x 43,7 x 50,8	32,5 (14,7)
5P1500R	1440/1100	5-15P	(5) 5-15R	4,3 (1U) x 43,7 x 55,4	43,5 (19,7)
Global Rackmount 208/230V, 50/60 Hz					
5P850GR	850/600	C14	(4) C13	4,3 (1U) x 43,7 x 50,8	30,4 (13,8)
5P1550GR	1550/1100	C14	(6) C13	4,3 (1U) x 43,7 x 55,4	42,7 (19,4)

UPS Eaton 5P Litio

1550 VA

120 V y 208/230 V

Núm. de Catálogo	Cap. Nominal (VA/watts)	Conexión de entrada	Receptáculos de salida	Medidas (A x A x P), cm	Peso neto, lb (Kg)
5P-Litio 1U Global Rackmount 208V/230V, 50/60Hz model					
5P1550GR-L	1550/1100	C14	(6) C13	4.3 x 43.7 x 55.4	35 (15.87)